


LAMP PHOTOMETRIC REPORT

MODEL: 92FLCOM4040/WH		
POWER: 40W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 3320.0 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	3758	3852	3882	3834	3738	3662	3615	3670	0- 10	394.8	394.8	11.9
20	2500	2600	2642	2548	2420	2347	2325	2387	10- 20	864.1	1259	37.9
30	1524	1581	1585	1577	1492	1439	1438	1471	20- 30	892.6	2152	64.8
40	1016	1089	1110	1055	965.0	889.3	843.3	916.4	30- 40	797.0	2949	88.8
50	55.05	62.38	64.37	55.57	49.57	46.31	43.35	47.47	40- 50	308.3	3257	98.1
60	27.38	28.71	29.41	28.27	26.97	25.53	25.86	26.01	50- 60	32.91	3290	99.1
70	15.89	16.58	15.47	15.75	15.60	15.01	14.28	14.38	60- 70	19.46	3309	99.7
80	2.138	2.043	1.720	2.140	2.477	1.991	1.695	1.682	70- 80	9.985	3319	100
90	0.1597	0.1535	0.1526	0.1556	0.2409	0.2363	0.2371	0.2321	80- 90	0.7571	3320	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:24 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```