


LAMP PHOTOMETRIC REPORT

MODEL: 93TLOM3040/WH		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2718.1 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	5147	4689	4590	4936	5535	5832	5827	5591	0- 10	684.1	684.1	25.2
20	1734	1678	1660	1755	1843	1922	1904	1863	10- 20	853.8	1538	56.6
30	990.3	965.5	958.9	979.9	1016	1036	1031	1016	20- 30	588.0	2126	78.2
40	143.7	128.7	133.6	141.2	144.0	206.8	172.9	143.6	30- 40	345.5	2471	90.9
50	86.25	85.10	88.00	90.27	90.36	88.60	88.67	86.97	40- 50	86.22	2558	94.1
60	56.39	55.01	55.14	56.73	58.33	59.55	59.79	58.37	50- 60	63.20	2621	96.4
70	43.64	42.55	42.90	44.03	45.23	46.20	46.27	45.29	60- 70	50.66	2672	98.3
80	19.59	19.27	19.90	20.91	21.84	22.13	21.67	20.68	70- 80	36.27	2708	99.6
90	0.3003	0.3012	0.3024	0.3019	0.3354	0.3582	0.3405	0.3265	80- 90	10.32	2718	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:19 October 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```