


LAMP PHOTOMETRIC REPORT

MODEL: 95Livial60/GR		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 828.11 lm



$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%
10	390.4	389.5	388.8	390.0	390.2	390.4	389.3	389.7	0- 10	37.52	37.52	4.53
20	364.2	362.8	362.5	361.5	365.1	367.0	364.6	366.0	10- 20	106.9	144.4	17.4
30	322.6	322.0	319.1	316.9	320.2	321.2	320.0	322.3	20- 30	158.5	302.9	36.6
40	261.2	260.0	256.1	252.9	253.7	255.2	256.2	259.3	30- 40	181.6	484.5	58.5
50	176.0	177.7	173.8	168.6	169.7	170.2	173.4	177.0	40- 50	167.0	651.4	78.7
60	86.52	84.51	82.08	79.44	75.90	81.08	82.81	85.64	50- 60	112.4	763.8	92.2
70	25.72	25.87	25.79	23.59	24.16	24.75	26.79	27.23	60- 70	49.96	813.8	98.3
80	3.478	3.367	3.292	3.384	3.511	3.635	3.671	3.775	70- 80	12.42	826.2	99.8
90	0.1931	0.1991	0.1991	0.2043	0.1636	0.1734	0.1691	0.1796	80- 90	1.907	828.1	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 10.0DEG  
Test Speed: MEDIUM  
Temperature:25.3°C  
Operators:  
Test Date:19 December 2022

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 2.5DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
Humidity:65.0%  
Test Distance:6.265m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```