


LAMP PHOTOMETRIC REPORT

MODEL: 98Vega10Slim		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 922.85 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	344.3	342.3	341.9	339.1	339.7	339.6	342.3	342.7	0- 10	32.78	32.78	3.55
20	332.1	328.7	326.4	322.8	323.8	324.2	328.3	329.8	10- 20	94.70	127.5	13.8
30	308.8	304.2	300.5	296.6	297.9	298.9	303.4	306.4	20- 30	145.5	273.0	29.6
40	273.2	268.5	264.3	260.0	260.6	262.9	268.3	271.8	30- 40	178.3	451.2	48.9
50	224.4	219.9	197.5	211.8	212.3	215.5	214.1	223.3	40- 50	185.8	637.0	69
60	158.8	144.7	121.3	137.5	140.6	150.1	129.5	156.2	50- 60	160.3	797.3	86.4
70	67.75	57.59	33.24	52.86	61.08	60.27	37.55	64.78	60- 70	96.77	894.0	96.9
80	5.329	4.821	3.857	4.647	4.996	7.790	5.673	8.341	70- 80	27.17	921.2	99.8
90	0.3103	0	0	0	0.4110	0	0	0	80- 90	1.623	922.8	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:01 July 2022

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks: