


LAMP PHOTOMETRIC REPORT

MODEL: 99LED607IP65		
POWER: 7W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 470.33 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	162.3	162.4	163.0	163.2	163.1	163.2	163.4	162.6	0- 10	15.67	15.67	3.33
20	153.4	153.7	154.7	155.0	155.4	155.2	155.3	154.6	10- 20	44.98	60.65	12.9
30	139.4	139.5	140.6	141.1	141.8	141.6	141.0	140.7	20- 30	68.33	129.0	27.4
40	120.2	120.3	121.3	122.0	122.7	122.8	122.4	121.3	30- 40	82.39	211.4	44.9
50	96.91	96.78	97.71	98.41	99.24	99.35	98.99	97.88	40- 50	85.06	296.4	63
60	70.91	70.47	71.00	71.78	72.69	72.84	72.35	71.68	50- 60	76.07	372.5	79.2
70	43.53	43.13	43.32	44.01	45.02	45.27	44.67	44.01	60- 70	57.30	429.8	91.4
80	17.58	17.26	17.31	17.88	18.70	18.92	18.39	17.86	70- 80	32.48	462.3	98.3
90	0.2316	0.2313	0.2317	0.2301	0.1935	0.2055	0.1990	0.1974	80- 90	8.032	470.3	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:10 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

MODEL: 99LED607IP65		
POWER: 7W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

UNIT: cd

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```